

SJ12/16 VERTICAL MASTS

Dimensions	SJ12	SJ16
A Work Height	5.65 m	6.75 m
B Raised Platform Height	3.65 m	4.75 m
C Lowered Platform Height	0.46 m	0.46 m
D Overall Width	0.78 m	0.78 m
E Overall Length	1.40 m	1.40 m
F Stowed Height	1.78 m	1.78 m
G Platform Width (Inside Dimension)	0.69 m	0.69 m
H Platform Length (Inside Dimension)	0.86 m	0.86 m
Specifications	SJ12	SJ16
Traversing Platform (Roll Out)	0.41 m	0.41 m
Ground Clearance (Pothole Raised)	5.3 cm	5.3 cm
Ground Clearance (Pothole Deployed)	1.3 cm	1.3 cm
Wheelbase	1.07 m	1.07 m
Weight	863 kg	980 kg
Gradeability	30%	30%
Turning Radius (Inside)	0	0
Turning Radius (Outside)	1.40 m	1.40 m
Lift Time (With Rated Load)	14 sec	21 sec
Lower time (With Rated Load)	15 sec	18 sec
Drive Speed (Stowed)	4.0 km/h	4.0 km/h
Drive Speed (Raised)	0.8 km/h	0.8 km/h
Maximum Drive Height	Full Height	Full Height
Capacity (Overall)	227 kg	227 kg
Local Floor Load (With Rated Load)	745 kN/m2	880 kN/m2
Overall Floor Load (With Rated Load)	1,040 kg/m2	1,152 kg/m2
Maximum # of Persons at 0 m/s wind rating	2	1
Maximum # of Persons up to 12.5 m/s wind rating	1	0 / Optional 1
Tyre Type	Solid, N/M	Solid, N/M
Tyre Size	12 x 4 x 8	12 x 4 x 8





www.skyjack.com

Skyjack UK Unit 1, Maes-y-Clawdd Maesbury Road Industrial Estate Oswestry, Shropshire, SY10 8NN Tel: +44 1691 676235 Fax: +44 1691 676239 Email: info@skyjackeurope.co.uk

Skyjack SAS (France) 74 Rue Sibert F-42400 Saint Chamond France Tel: +33 (0) 4 78 73 53 32 Fax: +33 (0) 4 78 56 52 42

Skyjack Hebebühnen GmbH (Germany) Därmannsbusch 2a D-58456 Witten Tel: +49 (0) 2302 20 26 909

Agnesbergsvägen 28 424 38 Agnesberg Sweden Tel: +46 (0) 31 21 22 45 Fax: +49 (0) 2302 20 25 671 Fax: +46 (0) 31 787 65 10

