

RENT AM7T

6000W 400V / 4400W 230V



TIPO / TYPE



EQUIPAMIENTO / FEATURES



DOTACIÓN / INCLUDED



EMBALAJE / PACKAGING



RECAMBIOS FRECUENTES / FREQUENT SPARE PARTS



Ref. 400001



Ref. 400064



Ref. 400016



Ref. 400040



Ref. 400046



Ref. 400056

MODELO / MODEL

Regulación - Voltaje - Frecuencia / Regulation - Voltage - Frequency

AC 400V Máxima / Maximum

AC 400V Nominal / Rated

AC 230V Máxima / Maximum

AC 230V Nominal / Rated

Modelo motor / Engine model

Cilindrada / Displacement

Tipo de motor / Engine type

Nivel de presión acústica media a 7mts LpA / Acoustic pressure level average at 7mts LpA

Nivel de potencia acústica garantizada LwA acorde 2000/14/EC enmienda 2005/88/EC

Guaranteed sound power level LwA pursuant to 2000/14/EC amended by 2005/88/EC

Tipo de arranque / Startup type

Capacidad tanque combustible / Fuel tank capacity

Consumo hora - Autonomía al 25% 50% 75% carga

Hourly consumption - Autonomy at 25% 50% 75% loads

Capacidad de aceite - Tipo aceite / Oil capacity - Type of oil

Kit de transporte / Transportation kit

Dimensiones sin/con ruedas L x A x Alto (cm) / Dimensions without/with wheels L x W x H (cm)

Peso máquina / bruto embalaje (Kg) / Machine weight / gross packaging (Kg)

Referencia / Reference

RENT AM7T

Estabilizador electrónico / Electronic stabilizer - 230/400V - 50Hz

6000W (7.5kVA)

fdp / pf 0.8

5500W (6.8kVA)

fdp / pf 0.8

4400W

4000W

GENENERGY SG150

420cc

Gasolina, 4 tiempos OHV refrigeración forzada por aire Gasoline, 4-stroke OHV, air forced cooling

74dB (A)

97dB (A)

Manual / Recoil

6.5L

(1.5 l/h - 4,3h) (1.8 l/h - 3,6h) (2,4 l/h - 2,7h)

1.1L SAE10W30 - SAE10W40

Si, con neumáticos de goma 10" y llanta metálica Yes, 10" rubber tires and metal rim

74 x 53 x 58 / 77 x 69 x 60

81 / 90

2013037